BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD





ATS Part#:

ATS-50350G-C1-R0

Description:

35.00 x 35.00 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD

 Heat Sink Type:
 maxiFLOW

 Heat Sink Attachment:
 maxiGRIP

 Equivalent Part Number:
 ATS-50350G-C2-R0 Discontinued

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- · Comes preassembled with high performance, phase changing, thermal interface material
- Designed for standard height components from 3 to 4.5mm

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 3 °C/W | 2.3 °C/W | 2 °C/W | 1.8 °C/W | 1.6 °C/W | 1.5 °C/W | 1.4 °C/W |
| | Ducted Flow | 2.2 | N/A | N/A | N/A | N/A | N/A | N/A |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | ТІМ | Finish |
|--|--|--|---|---|---------------------------------------|--|
| | 35.00 mm | 35.00 mm | 12.50 mm | 57.2 mm | T766 | BLUE-ANODIZED |
| | Dimension ATS-5035 (Saint Gol Thermal p application ATS resen performan ATS certifi Optional n | 0G-C2-R0 is the exa bain C1100F). NOTE performance data are n. ves the right to upda nce. ies that this heat sint maxiGRIP™ Installat | mponent size. eight from the botton ict heat sink assembl : Saint Gobain C110 provided for referen te or change its prod c assembly is RoHS- ion/Removal Tool Se stom options availab | y with an equivalent 0F is discontinued ef ce only. Actual perfo lucts without notice to 6 and REACH comp at P/N: MGT350 | thermal in ffective 12 rmance m | nterface material 2/31/10. nay vary by |
| *Image above is for illustration purpose only. | | | | | | |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA