

## Low drop power Schottky rectifier


### Features

- Very small conduction losses
- Negligible switching losses
- Low forward voltage drop
- Surface mount miniature packages
- Avalanche capability specified

### Description

Single chip Schottky rectifiers suited to switched mode power supplies and high frequency DC to DC converters.

Packaged in SMA, SMB and STmite flat this device is especially intended for surface mounting and used in low voltage, high frequency inverters, free wheeling and polarity protection applications.



**Table 1. Device summary**

Symbol	Value
$I_{F(AV)}$	1 A
$V_{RRM}$	40 V
$T_j$ (max)	150 °C
$V_F$ (max)	0.42 V

# 1 Characteristics

**Table 2. Absolute ratings (limiting values)**

Symbol	Parameter			Value	Unit
$V_{RRM}$	Repetitive peak reverse voltage			40	V
$I_{F(RMS)}$	Forward rms current	SMA / SMB			8
		STmite flat			2
$I_{F(AV)}$	Average forward current	SMA / SMB	$T_L = 130 \text{ }^\circ\text{C}$	$\delta = 0.5$	1
		STmite flat	$T_C = 135 \text{ }^\circ\text{C}$	$\delta = 0.5$	
$I_{FSM}$	Surge non repetitive forward current	$t_p = 10 \text{ ms}$	sinusoidal		60
$I_{RRM}$	Repetitive peak reverse current	$t_p = 2 \mu\text{s}$	$F = 1 \text{ kHz}$ square		1
$I_{RSM}$	Non repetitive peak reverse current	$t_p = 100 \mu\text{s}$	square		1
$P_{ARM}$	Repetitive peak avalanche power	$t_p = 1 \mu\text{s}$	$T_j = 25 \text{ }^\circ\text{C}$		900
$T_{stg}$	Storage temperature range			- 65 to + 150	$^\circ\text{C}$
$T_j$	Maximum operating junction temperature <sup>(1)</sup>			150	$^\circ\text{C}$
$dV/dt$	Critical rate of rise of reverse voltage			10000	V/ $\mu\text{s}$

1.  $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$  condition to avoid thermal runaway for a diode on its own heatsink

**Table 3. Thermal resistance**

Symbol	Parameter			Value	Unit
$R_{th(j-l)}$	Junction to lead	SMA	30	°C/W	
		SMB	25		
$R_{th(j-c)}$	Junction to case	STmite flat	20		

**Table 4. Static electrical characteristics**


Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
$I_R$ <sup>(1)</sup>	Reverse leakage current	$T_j = 25 \text{ }^\circ\text{C}$	$V_R = V_{RRM}$	-	-	35	$\mu\text{A}$
		$T_j = 125 \text{ }^\circ\text{C}$		-	6	10	mA
$V_F$ <sup>(1)</sup>	Forward voltage drop	$T_j = 25 \text{ }^\circ\text{C}$	$I_F = 1 \text{ A}$	-	-	0.5	V
		$T_j = 125 \text{ }^\circ\text{C}$		-	0.37	0.42	
		$T_j = 25 \text{ }^\circ\text{C}$	$I_F = 2 \text{ A}$	-	-	0.63	
		$T_j = 125 \text{ }^\circ\text{C}$		-	0.5	0.61	

1. Pulse test:  $t_p = 380 \mu\text{s}$ ,  $\delta < 2\%$


To evaluate the conduction losses use the following equation:

$$P = 0.23 \times I_{F(AV)} + 0.19 I_F^2 \text{ (RMS)}$$


**Figure 1. Average forward power dissipation versus average forward current**




**Figure 3. Average forward current versus ambient temperature (SMB,  $\delta = 0.5$ )**




**Figure 5. Normalized avalanche power derating versus pulse duration**




**Figure 2. Average forward current versus ambient temperature (SMA,  $\delta = 0.5$ )**




**Figure 4. Average forward current versus ambient temperature (STmite flat,  $\delta = 0.5$ )**




**Figure 6. Normalized avalanche power derating versus junction temperature**




**Figure 7.** Non repetitive surge peak forward current versus overload duration (maximum values, SMA)




**Figure 9.** Non repetitive surge peak forward current versus overload duration (maximum values, STmite flat)




**Figure 11.** Relative variation of thermal impedance junction to ambient versus pulse duration (SMB)




**Figure 8.** Non repetitive surge peak forward current versus overload duration (maximum values, SMB)




**Figure 10.** Relative variation of thermal impedance junction to ambient versus pulse duration (SMA)




**Figure 12.** Relative variation of thermal impedance junction to ambient versus pulse duration (STmite flat)




**Figure 13. Reverse leakage current versus reverse voltage applied (typical values)**




**Figure 15. Forward voltage drop versus forward current (typical values, high level)**




**Figure 14. Junction capacitance versus reverse voltage applied (typical values)**




**Figure 16. Forward voltage drop versus forward current (typical values, low level)**




**Figure 17.** Thermal resistance junction to ambient versus copper surface under each lead (SMA)



**Figure 18.** Thermal resistance junction to ambient versus copper surface under each lead (SMB)



**Figure 19.** Thermal resistance junction to ambient versus copper surface under tab (STmite flat)




## 2 Package information

- Epoxy meets UL94, V0
- Cathode band (SMA, SMB)


In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com).  
ECOPACK® is an ST trademark.

**Table 5. SMA dimensions**

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.094
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.40	0.006	0.016
D	2.25	2.90	0.089	0.114
E	4.80	5.35	0.189	0.211
E1	3.95	4.60	0.156	0.181
L	0.75	1.50	0.030	0.059




**Figure 20. Footprint, dimensions in mm (inches)**




**Table 6. SMB dimensions**

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.096
A2	0.05	0.20	0.002	0.008
b	1.95	2.20	0.077	0.087
c	0.15	0.40	0.006	0.016
D	3.30	3.95	0.130	0.156
E	5.10	5.60	0.201	0.220
E1	4.05	4.60	0.159	0.181
L	0.75	1.50	0.030	0.059

**Figure 21. Footprint, dimensions in mm (inches)**

**Table 7.** STmite flat dimensions

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	0.80	0.85	0.95	0.031	0.033	0.037
b	0.40	0.55	0.65	0.016	0.022	0.026
b2	0.70	0.85	1.00	0.027	0.033	0.039
c	0.10	0.15	0.25	0.004	0.006	0.009
D	1.75	1.90	2.05	0.069	0.075	0.081
E	3.60	3.80	3.90	0.142	0.150	0.154
E1	2.80	2.95	3.10	0.110	0.116	0.122
L	0.50	0.55	0.80	0.020	0.022	0.031
L1	2.10	2.40	2.60	0.083	0.094	0.102
L2	0.45	0.60	0.75	0.018	0.024	0.030
L3	0.20	0.35	0.50	0.008	0.014	0.020

**Figure 22.** Footprint dimensions

### 3 Ordering information

**Table 8. Ordering information**

Order code	Marking	Package	Weight	Base qty	Delivery mode
STPS1L40A	GB4	SMA	0.068 g	5000	Tape and reel
STPS1L40U	GC4	SMB	0.107 g	2500	Tape and reel
STPS1L40MF	F1L4	STmite flat	0.016 g	1200	Tape and reel

### 4 Revision history

**Table 9. Document revision history**

Date	Revision	Changes
Jul-2003	4A	Last update.
Aug-2004	5	SMA package dimensions update. Reference A1 max. changed from 2.70 mm (0.106 inch.) to 2.03 mm (0.080).
24-Jun-2009	6	Added STmite flat package.

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)

