


HSK-MZ-EMC

Metr., Metr.-elongated, PG, PG-elongated, NPT



| | |
|-----------------------|---|
| Material | Nickel plated brass |
| Clamping insert | Polyamide |
| Seal | Buna-N |
| O-Ring | Buna-N |
| Protection | IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) |
| Operating Temperature | -40 °C – 100 °C (-40 °F – 212 °F) |

// Other sealing materials e.g. silicone upon request
 // Also available in PVDF, -35 °C – 150 °C *



| AG | ∅k mm | H mm | R mm | GL mm | Number | GL mm | Number elongated |
|------------|----------|---------|---------|----------|---------------|----------|---------------------|
| M 12 x 1,5 | 3–6,5 | 26 | 14 | 6,5 | 1.692.1200.50 | 10 | 1.692.1200.30 |
| M 16 x 1,5 | 6–10 | 29 | 20 | 6 | 1.692.1600.50 | 10 | 1.692.1600.30 |
| M 20 x 1,5 | 10–14 | 32 | 24 | 6 | 1.692.2000.50 | 10 | 1.692.2000.30 |
| M 25 x 1,5 | 13–18 | 35 | 30 | 7 | 1.692.2500.50 | 12 | 1.692.2500.30 |
| M 32 x 1,5 | 18–25 | 41 | 40 | 8 | 1.692.3200.50 | 12 | 1.692.3200.30 |
| M 40 x 1,5 | 22–32 | 48 | 50 | 8 | 1.692.4000.50 | 15 | 1.692.4000.30 |
| M 50 x 1,5 | 32–38 | 51 | 57 | 9 | 1.692.5000.50 | 15 | 1.692.5000.30 |
| M 50 x 1,5 | 25–31 | 51 | 57 | 9 | 1.692.5000.51 | 15 | 1.692.5000.31 |
| M 63 x 1,5 | 37–44 | 52 | 64/68 | 10 | 1.692.6300.50 | 15 | 1.692.6300.30 |
| M 63 x 1,5 | 29–35 | 52 | 64/68 | 10 | 1.692.6300.51 | 15 | 1.692.6300.31 |
| PG 7* | 3–6,5 | 26 | 14 | 5 | 1.692.0700.01 | 10 | 1.692.0700.60 |
| PG 9* | 4–8 | 28 | 17 | 6 | 1.692.0900.01 | 10 | 1.692.0900.60 |
| PG 11* | 6–10 | 29 | 20 | 6 | 1.692.1100.01 | 10 | 1.692.1100.60 |
| PG 13,5* | 6–12 | 33 | 22 | 6,5 | 1.692.1300.01 | 10 | 1.692.1300.60 |
| PG 16* | 10–14 | 32 | 24 | 6,5 | 1.692.1600.01 | 10 | 1.692.1600.60 |
| PG 21* | 13–18 | 35 | 30 | 7 | 1.692.2100.01 | 12 | 1.692.2100.60 |
| PG 29* | 18–25 | 41 | 40 | 8 | 1.692.2900.01 | 12 | 1.692.2900.60 |
| PG 36* | 22–32 | 48 | 50 | 8 | 1.692.3600.01 | 15 | 1.692.3600.60 |
| PG 42* | 32–38 | 51 | 57 | 9 | 1.692.4200.01 | 15 | 1.692.4200.60 |
| PG 42* | 25–31 | 51 | 57 | 9 | 1.692.4200.15 | 15 | 1.692.4200.61 |
| PG 48* | 37–44 | 51 | 64 | 10 | 1.692.4800.01 | 15 | 1.692.4800.60 |
| PG 48* | 29–35 | 51 | 64 | 10 | 1.692.4800.15 | 15 | 1.692.4800.61 |
| NPT 3/8" | 4–8 | 28 | 17/19 | 15 | 1.692.3800.70 | | |
| NPT 1/2" | 6–12 | 29 | 22/24 | 13 | 1.692.1200.70 | | |
| NPT 3/4" | 13–18 | 35 | 30 | 13 | 1.692.3400.70 | | |

