Предохранитель, низкое напряжение, 10 A, AC 500 V, D1, 13.2 x 6 mm, gR, IEC, Fast acting

Powering Business Worldwide

№ для зак. 10D16Q
Каталог № 10D16Q

Программа поставок

Программа поставок			Предохранитель
Основная функция			Предохранитель
Область применения			низкое напряжение
Номинальный ток	I	A	10
Номинальное напряжение			AC 500 V
Типоразмер			D1
Типоразмер			13,2 x 6 мм
Категория применения			gR
Отключающая способность		кА	50
возможно использование для типоразмеров/оборудования			E16 для бытового и промышленного применения
Характеристика размыкания	Класс		Быстрого действия
Стандарт/сертификат			IEC
Форма			бутылочная форма
Стандарты/предписания			IEC 60269-3 VDE 0636

Технические характеристики согласно ETIM 6.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ecl@ss8.1-27-14-20-04 [AFZ799012])

Construction size			DI
Nominal rated current		A	10
Nominal rated voltage		V	500
Colour code			Red
Utilization category			gR (general purpose semiconductor protection)
Release characteristic			Fast (F)

© 11/2012 by Eaton Industries GmbH