

SKINDICHT® MA-M/PG

SKINDICHT® MA-M/PG, adapter, enables the use of PG accessories in metric threads



Robust



Mechanical resistance

Benefits

Enables the use of PG accessories in metric threads

Application range

Adapter from a metric outer thread to a PG inner thread.

Machines

Devices

Housings

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

On request:

with O-ring fitted

Material:

Nickel-plated brass

Temperature range:

-60°C to +200°C

SKINDICHT® MA-M/PG**Note**

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINDICHT® MA-M/PG**

Article number	Thread, male M1	Thread, female PG/NPT
SKINDICHT® MA-M / PG		
52104200	16 x 1.5	7
52104210	20 x 1.5	9
52104220	25 x 1.5	11
52104230	25 x 1.5	13.5
52104240	25 x 1.5	16
52104250	32 x 1.5	16
52104260	32 x 1.5	21
52104270	40 x 1.5	21
52104280	50 x 1.5	29
52104290	63 x 1.5	36
52104300	63 x 1.5	42

Last Update (05.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16