



Schaltplan
Wiring diagram

Nr. / No.	Beschreibung / Description
70661	HiEnd SAT Antenna cable F/F 1.00 m black
70598	HiEnd SAT Antenna cable F/F 1.00 m white
70664	HiEnd SAT Antenna cable F/F 2.00 m black
70600	HiEnd SAT Antenna cable F/F 2.00 m white
70666	HiEnd SAT Antenna cable F/F 3.00 m black
70606	HiEnd SAT Antenna cable F/F 3.00 m white
70672	HiEnd SAT Antenna cable F/F 5.00 m black
70644	HiEnd SAT Antenna cable F/F 5.00 m white
70678	HiEnd SAT Antenna cable F/F 10.00 m black
70653	HiEnd SAT Antenna cable F/F 10.00 m white

SAT Antennenkabel

- Ideal für hochauflösende Übertragungen (HD-TV, Full HD, Ultra HD (UHD / 4K und höher) bei digitalen SAT-Signalen wie DVB-S und DVB-S2. Zuverlässige Verbindung zwischen Anschluss-/ Multimediodose und dem Empfangsgerät wie Fernseher/ Sat-Receiver/ Kabelmodem/ Kabelrouter etc.
- Anschlüsse: F-Stecker
- OFC Innenleiter
- PVC/PE Ummantelung
- 4-fache Schirmung: (2-fach AlMg Geflecht und 2-fach Al Folie)
- 135 dB Schirmungsmaß
- Vollmetall-Stecker mit vergoldeten Kontakten
- breite, griffige Metallkappen
- optimierter Knickschutz und flexible Kabelummantelung
- Isolationswiderstand: 10 Ohm bis 500 V DC
- Durchschlagsfestigkeit: 1 kV, 50 Hz, 2 s
- Konformität: RoHS/REACH

SAT antenna cable

- ideal for high-resolution transmissions (HDTV, Full HD, Ultra HD (UHD/4K and higher)) for both digital SAT signals such as DVB-S and DVB-S2. Reliable connection between the wall/ multimedia outlet and the receiving device, such as a TV/SAT receiver, cable modem, cable router etc.
- Connections: F male connector
- OFC inner conductor
- PVC / PE sheath
- 4-fold shielding: (2-fold AlMg mesh and 2-fold Al foil)
- 135 dB shielding measure
- Full metal plug with gold plated contacts
- wide, handy metal caps
- optimized kink protection and flexible cable sheathing
- Insulation resistance: 10 Ohms to 500 V DC
- Dielectric strength: 1 kV, 50 Hz, 2 s
- Conformity: RoHS / REACH

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	24.09.2018	HiEnd SAT Antenna cable F/F	
		gepr.:	24.09.2018		
		Norm:		Zeichnungs-Nr.:	von
Änderungen vorbehalten / Subject to change					

