BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD





ATS Part#:

ATS-50330P-C1-R0

Description:

33.00 x 33.00 x 17.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD

 Heat Sink Type:
 maxiFLOW

 Heat Sink Attachment:
 maxiGRIP

 Equivalent Part Number:
 ATS-50330P-C2-R0 Discontinued

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- · Comes preassembled with high performance, phase changing, thermal interface material
- Designed for standard height components from 3 to 4.5mm

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	2.7 °C/W	2.1 °C/W	1.9 °C/W	1.7 °C/W	1.5 °C/W	1.4 °C/W	1.4 °C/W
	Ducted Flow	2.1	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	33.00 mm	33.00 mm	17.50 mm	58.2 mm	T766	BLUE-ANODIZED
	 Dimension ATS-5033 (Saint Gol Thermal p application ATS reserve performar ATS certifinities Optional reserve performant 	ves the right to upda	eight from the bottor ct heat sink assembl : Saint Gobain C110 provided for referen te or change its proc assembly is RoHS- ion/Removal Tool Se	y with an equivalent OF is discontinued e ce only. Actual perfo lucts without notice t 6 and REACH comp et P/N: MGT330	thermal in ffective 12 rmance n o improve	nterface material 2/31/10. nay vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA

