



NOTES:

1. TERMINAL TO BE USED IN HOUSING 70066-\*\*\*\* AND 70450-\*\*\*\*.
2. REFER TO PRODUCT SPECIFICATION PS-70058.
3. REFER TO MOLEX OPERATIONS AND SERVICE MANUAL FOR CRIMP DETAILS.
4. TERMINAL TO BE USED WITH  $(0.64) / .025$  SQUARE PINS.
5. TERMINAL TO BE USED WITH 22-24 AWG STRANDED WIRE WITH  $(1.63) / .064$  MAXIMUM DIAMETER INSULATION.
6. TERMINALS SUPPLIED IN REEL FORM.
7. CRIMP SIZE INDICATOR C=22-24 AWG

PLATING:

.000150 MINIMUM TIN PLATE IN SELECT AREA,  
OVER NICKEL PLATE OVERALL.

REEL UNWIND DIR EC NO: UCP2013-5345 DRAWN: RWHIPPLE 2013/06/11 CHKD: DMORGAN 2013/06/11 APPR: SMILLER 2013/07/09	DESCRIPTION QUALITY SYMBOLS $\nabla = 0$ $\nabla = 0$ $\nabla = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
				MM/IN	10:1	INCH		
				DRAWN BY	DATE	TITLE		
				CHECKED BY	DATE	TERMINAL - BOX/CRIMP FOR 22-24 AWG ON A REEL		
		APPROVED BY		DATE	DOCUMENT NO.			
		MATERIAL NO.		DATE	SHEET NO.			
		16-02-0086		2013/07/09	1 OF 1			
		SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				