

ВИЛОЧНЫЕ НАКОНЕЧНИКИ


DIN 46237

Материал наконечника: электротехническая медь

Поверхность: луженая

Изолирующая трубка ПА, без галогенов

Температура: до 105° C



Сечение мм²	Отверстие Ø	Артикул	Параметры, мм									Инстру- менты	 100 шт. ~ кг	 шт.
			d ₁	d ₂	d ₃	d ₄	l	a ₁	a ₂	s				
0.1 – 0.4	3.5 – 0.5	619C/3*	–	3.2	5	–	14	–	–	0.5	Стр. 8.24- 8.25	0.020	100	
0.5 – 1	3.5 – 1	620C/3	1.6	3.2	6	4.5	16.5	5	10.5	0.8		0.060	100	
	3.5 – 1	620C/3.5		3.7	6.8		17.5					0.060	100	
	4.5 – 1	620C/4		4.3	6.8		17.5					0.070	100	
	5.5 – 1	620C/5		5.3	10		18.5					0.090	100	
	6.5 – 1	620C/6		6.5	11		20.5					0.080	100	
1.5 – 2.5	3.5 – 2.5	630C/3	2.3	3.2	6	5.1	17.5	5	11.5	0.8		0.060	100	
	3.5 – 2.5	630C/3.5		3.7	6.8		18.5					0.065	100	
	4.5 – 2.5	630C/4		4.3	6.8		18.5					0.080	100	
	5.5 – 2.5	630C/5		5.3	10		20.5					0.090	100	
	6.5 – 2.5	630C/6		6.5	11		22.5					0.110	100	
4 – 6	4.5 – 6	650C/4	3.6	4.3	8	6.4	20.5	6	12.5	1		0.140	100	
	5.5 – 6	650C/5		5.3	10		21.5					0.160	100	
	6.5 – 6	650C/6		6.5	11		22.5					0.170	100	
	8.5 – 6	650C/8		8.4	14		25.5					0.220	100	
	10.5 – 6	650C/10		10.5	18		27.5					0.280	100	

ШТЫРЕВЫЕ НАКОНЕЧНИКИ


DIN 46231

Материал наконечника: электротехническая медь

Поверхность: луженая

Изолирующая трубка ПА, без галогенов

Температура: до 105° C



Сечение мм²	Номинал DIN	Артикул	Параметры, мм								Инстру- менты	 100 шт. ~ кг	 шт.
			d ₃	d ₄	l ₁	l ₂	a ₁	a ₂	s				
0.1 – 0.4	0.5	704*	1.4	–	18	9	–	–	0.5	Стр. 8.24- 8.25	0.020	100	
0.5 – 1	1	705 K* 705	1.9	3.2	18 22	6 10	5	10.5	0.8		0.060	100	
											0.065	100	
1.5 – 2.5	2.5	710 K* 710 710 L*	1.9	3.9	19.5 23 27.5	6.5 10 16	5	11.5	0.8		0.060	100	
										0.065	100		
										0.100	100		
4 – 6	6	715	2.9	5.6	26	11	6	12.5	1	0.160	100		

* Нестандартный