MILAN S.r.l. a socio unico

Head Office – Export department:
Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

FirestoP®

Technical Datasheet

tasker® C3025 CPR – 3x0,25 mm² Braided Shielded Cable

A	B	C	D

NOTE The picture does not represent the real number of conductors

CATEGORY Braided Conductor Shielded Cable **(**See Data Network Catalogue)

APPLICATIONS Data transmission and Electronics

A: Black **Flame Retardant PVC** sheath.
Outer cable diam. Ø 5,00 (±0,20) mm.

B: Braided Shielding O.F.C. Red Copper covering 85%.

C: Cores Insulation with **Flame Retardant PVC.**
Core color code with DIN 47100 Standards.
Diam. Ø 1,40 (±0,20) mm.

D: Stranded O.F.C. Red Copper formation 8x0,20 mm.
Nom. Cross section 3x0,25 mm².

MARKING **tasker®** C3025 CPR 3x0,25 mm² O.F.C. - IMQ 0051-CPR-0966 – 2017 – Eca – BRAIDED SHIELDED CABLE - Firestop® - Made Italy

Cable Properties

Conductor Resistance	75,85 Ω/Km
Capacity Core/Core	150 pF/m
Capacity Core/Shield	290 pF/m
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS3 Compliant
Informazioni	X	Ver. B / 26.05.19