BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD





ATS Part#:

ATS-50425B-C1-R0

Description:

42.50 x 42.50 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD

Heat Sink Type: maxiFLOW Heat Sink Attachment: maxiGRIP Equivalent Part Number: ATS-50425B-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling .
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop . Testing standards
- Comes preassembled with high performance thermal interface material .
- Designed for standard height components from 3 to 4.5mm .

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.3 °C/W	3.2 °C/W	2.8 °C/W	2.4 °C/W	2.2 °C/W	2.1 °C/W	1.9 °C/W
	Ducted Flow	3	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	42.50 mm	42.50 mm	7.50 mm	58.9 mm	T412	BLUE-ANODIZED
	 Dimension ATS-5042 (Saint-Gol Thermal p application ATS resen performan ATS certifi Optional n 	5B-C2-R0 is the exa bain C675). erformance data are n. ves the right to upda uce. ies that this heat sint maxiGRIP™ Installat	eight from the bottor ct heat sink assembl provided for referen te or change its proc		thermal in rmance n o improve	nterface material nay vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



Rev - 011018

© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA