

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

Technical Datasheet

tasker® RG 11 AU

Mil. C 17 F Standard Coaxial Cable 75 Ω



CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS Standard Video signal transmission

- A:** Black soft **PVC** sheath.
Outer cable Diam. Ø 10,30 (±0,10) mm.
- B:** Shielding in O.F.C. red copper Braid covering 98%.
- C:** Core Insulation with transparent compact PE.
Diam. Ø 7,30 (±0,10) mm.
- D:** Stranded O.F.C. Tinned Copper Formation 7x0,40 mm.
Nom. Cross section 1x0,88 mm².

MARKING MIL-C-17 F RG11 AU 75 ohm
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	21 Ω/Km
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Operative Temperature	-15/+70°C

Attenuation db/100 mt

50 MHz	5,80
100 MHz	8,50
200 MHz	12,50
400 MHz	18,00
800 MHz	26,50
1 GHz	30,40

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			