

## DRAWING

HDD15PIN PLUG(P1)	WIRE	HDD15PIN PLUG(P2)
1		1
2		2
3		3
4		4
5		5
6		6
7		7
8		8
10		10
11		11
12		12
13		13
14		14
15		15
SHELL	D.W	SHELL

## 1.CABLE:NO UL 14C+1.((28AWG,7/0.12mm±0.008)×14C SHIELD:DRAIN WIRE+AL/MY COVERAGE

JACKET:PVC,COMPLIANCE ROHS,COLOR:BEIGE,O.D:6mm±0.2mm

2.CONNECTOR: 2 PCS HDD15 PIN MALE SOLDER TYPE CONNECTOR

SHELL:NICKEL PLATED

3.HDDD:PVC MOLDED TYPE WITH AL-FOIL SHIELDED ON INNER MOLD INJECTION DUTER MOLD WITH THUMB SCREW#4-40UNC HODD COLOR IS BEIGE, COMPLIANCE ROHS

4.Fulfill ROHS Guideline

5.ELECTRONIC TEST: 100% OPEN SHORT+MISS WIRE TEST

PART N□ C-15WWHD/1,8	SHEET NO 1	THIRD ANGLE PROJECTION
TITLE: HDD15 PIN PLUG TO HDD15 PIN F	PLUG	SCALE N.T.S DRAWN BY & DATE
BEIGE COLOR,L:1.8M		SIZE A4 CHECKED BY & DATE
		→ ☑ □ APPR□VED BY & DATE
DWN N□  D-C-15WWHD/1,8		mm INCH

