



## CATV-Drop-Cable RG6 (Cu) 77% PVC

## S677WVCU

**Application**

Installation cable used in professional networks, distributing TV signal and also applied as an aerial cable for terrestrial and satellite broadcast systems.

**Construction**

		<u>Diameter</u>
Inner conductor	copper [Cu]	Ø <b>1.02</b> ± 0.01 mm
Insulation	physical foamed PE, natural color	Ø <b>4.57</b> ± 0.13 mm
Outer conductor	tape [AL-PET] bonded	
Inner foil	aluminum braid, optical coverage 77%	
Shield	white PVC	Ø <b>6.91</b> ± 0.20 mm
Jacket		

**Electrical properties at 20 °C**

<b>Impedance</b>		Ω	75 ± 2
<b>Max attenuate</b>	5 MHz	dB/100m	1.92
	55 MHz	dB/100m	5.06
	211 MHz	dB/100m	9.82
	250 MHz	dB/100m	10.67
	350 MHz	dB/100m	12.59
	400 MHz	dB/100m	13.43
	450 MHz	dB/100m	14.32
	500 MHz	dB/100m	15.18
	550 MHz	dB/100m	15.97
	600 MHz	dB/100m	16.68
	750 MHz	dB/100m	18.43
	865 MHz	dB/100m	19.97
	1000 MHz	dB/100m	21.37
	1200 MHz	dB/100m	23.83
	1450 MHz	dB/100m	23.16
	1750 MHz	dB/100m	28.97
<b>Shielding effectiveness</b>		dB	> 95
<b>Propagation velocity</b>		%	85
<b>Resistance DC</b>			
Inner conductor		Ω/km	21
Outer conductor		Ω/km	30
<b>Return loss</b>			
5 - 1000 MHz		dB	≥ 20
<b>Nominal capacitance</b>		pF/m	53.2

**Technical data**

Product code	Cable type	Standard length [m]	Package dimensions high [cm] width [cm] depth [cm]	Minimum bend radius [mm]
S677WVCU	Coaxial cable RG6 copper (Cu) 77% PVC white	100, 250, 305	23x41x41 (305 m)	35

All rights of changes are reserved by manufacturer