



Click [here](#) for the 3D model.

### Dimensions

|             |                 |
|-------------|-----------------|
| D           | 6.3mm +/-0.5mm  |
| L           | 8mm +/-1mm      |
| S           | 2.5mm +/-0.5mm  |
| LL Negative | 15mm MIN        |
| LL Positive | 19mm MIN        |
| F           | 0.5mm +/-0.05mm |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 1000      |

### General Information

|              |                                |
|--------------|--------------------------------|
| Series       | A758                           |
| Dielectric   | Polymer Aluminum               |
| Description  | Single Ended, Polymer Aluminum |
| RoHS         | Yes                            |
| Lead         | Wire Leads                     |
| AEC-Q200     | No                             |
| Halogen Free | Yes                            |

### Specifications

|                       |                                                                          |
|-----------------------|--------------------------------------------------------------------------|
| Capacitance           | 330 uF                                                                   |
| Capacitance Tolerance | 20%                                                                      |
| Voltage DC            | 2.5 VDC, 2.9 VDC (Surge)                                                 |
| Temperature Range     | -55/+105°C                                                               |
| Rated Temperature     | 105°C                                                                    |
| Life                  | 5000 Hrs (+/-20% Initial Capacitance, 1.5x DF MAX, Leakage Within Limit) |
| Dissipation Factor    | 10% 120Hz 20C                                                            |
| Resistance            | 18 mOhms (100kHz 20C)                                                    |
| Ripple Current        | 3100 mAmps (100kHz 105C)                                                 |
| Leakage Current       | 123.75 uA (2min 20°C)                                                    |