


FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

The shaded part is illuminated

PANEL CUTOUT
MAX.PANEL THICKNESS
10 mm

Seal Ring



Contact Composition
1、2、3、4 are one set;
1,2 are normal closed(NC);
3,4 are normal opened(NO).

Part Number:GQ30-□■D/△/▲/◎

"□"	Contact structure	"■"	Operation mode	" "	Lamp Color	"▲"	Lamp Voltage	" "	Crust material
11	1NO1NC	No Letter	Momentary	R	Red	6V	AC/DC 6V	S	Stainless steel
22	2NO2NC	Z	Latching	G	Green	12V	AC/DC 12V	A	Al alloy(black)
				Y	Yellow	24V	AC/DC 24V		
				B	Blue	110V	AC/DC 110V		
				W	White	220V	AC/DC 220V		

Other voltage can be made to order

SPECIFICATIONS:

- Switch Rating: AC220V/2A, DC220V/0.1A.
- Mechanical Life: ≥1,000,000cycles.
- Electrical Life: ≥50,000cycles.
- Contact Resistance: ≤50mΩ.
- Insulation Resistance: ≥1,000MΩ.
- Dielectric Strength: 1,500V, RMS 50Hz, 1min.
- Operating Temperature: -25°C~ +55°C(No Freezing).
- Operating Force: About 5N(1NO1NC)/About 7.5N(2NO2NC).
- Operating Travel: About 2.5mm.
- Torque: About 0.6Nm max.applied to nut.
- IP Class: IP65,IP67(Momentary can made to order).
- Terminal Type: Pin Terminal(2.8 x 0.5mm).

MATERIALS:

- Contact: Silver alloy.
- Button: ◎.
- Body: ◎.
- Base: PA.

BRAND 品牌 **ONPOW** 红波按钮制造有限公司 ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

用途	APPD 审核	CH 2020/04/26
处理	CHKD 校对	NCH 2020/04/26
SCALE 比例 0.9 / 1	UNIT 单位 mm	DR. 制图 ZPD 2020/04/26
DIMENSIONS	TOLERANCE	TITLE 名称 GQ Series Anti-vandal push button
0.00 TO 18.00mm	±0.43mm	DWG NO. 图号 GQ30-D
18.01 TO 30.00mm	±0.52mm	
30.01 TO 50.00mm	±0.62mm	
50.01 TO 80.00mm	±0.74mm	
档案名称 GQ30-D.DWG	SHEET 张 1 / 1	REV. 更改 1

SIZE 图纸 A4