
KEMET Part Number: C44PXGR5330RASK



C44P-R, Film, Metallized Polypropylene, AC Filter, 33 uF, 10%, 1000 VAC, 2300 VDC



| Dimensions | | |
|------------|---------------|--|
| D | 75mm +/-0.5mm | |
| L | 247mm +/-2mm | |
| S | 35mm +/-1mm | |

| Packaging Specifications | | |
|--------------------------|---------------|--|
| Mounting: | Bolt - M12x16 | |
| Packaging: | Bulk, Bag | |

| General Information | | |
|---------------------|------------------------------|--|
| Series: | C44P-R | |
| Dielectric: | Metallized Polypropylene | |
| Style: | Can | |
| Features: | Single Phase PFC | |
| RoHS: | Yes | |
| Lead: | Threaded Studs M10 | |
| Miscellaneous: | Thermal Resistance = 5.3 C/W | |

| Specifications | |
|------------------------|--------------------------|
| Capacitance: | 33 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 1000 VAC |
| Voltage DC: | 2300 VDC |
| Temperature Range: | -25/+70°C |
| Rated Temperature: | 70°C |
| Dissipation Factor: | 0.02% 25C |
| Max dV/dt: | 85 V/us |
| Resistance: | 1.65551344 mOhms (10kHz) |
| Ripple Current: | 40 Amps (10kHz 40C) |
| Inductance: | 165 nH |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

