



ELECTRICAL RATINGS				MAGNETIC CHARACTERISTICS		
CONTACT FORM			A	TEST COIL L4989		
CONTACT RATING		WATTS	10			
RATING SENSITVITY		AMPERE TURNS		STANDARD TOLERANCE		
		20		PULL-IN RANGES		
VOLTAGE	SWITCHING	VDC-MAX.	200	12-23		
	BREAKDOWN	VDC-MIN	250	17-28		
	ARC-QUENCH	VDC-MIN	200	22-33		
CURRENT	SWITCHING	AMPERES-MAX.	0.5	27-38		
	CARRY	AMPERES-MAX.	1.2	TIGHTENED TOLERANCE		
RESISTANCE	CONTACT, INITIAL	OHMS-MAX.	0.10	PULL-IN RANGES		
	INSULATION	OHMS-MIN.	10 10	12-18		
CAPACITANCE		PICOFARADS-TYP.	0.2	17-23		
				22-28		
				27-33		
				32-38		

OPERATING CHARACTERISTICS			
OPERATE TIME		ms-MAX.	0.6
RELEASE TIME		ms-MAX.	0.2
SHOCK	G's MAX., 11ms 1/2 SINE WAVE		100
VIBRATION	G's MAX., 50-2000 HERTZ		30
RESONANT FREQUENCY		HERTZ, TYP.	3900
TEMPERATURE OPERATING		DEGREES, CELSIUS	-40 TO +125
		STORAGE	DEGREES, CELSIUS
SEE REED SWITCH CATALOG FOR DEFINITION OF TERMS			

DROP-OUT (DESIGN PARAMETER)

EXAMPLE:
17-33 AT PULL-IN
8-21 AT DROP-OUT

DRAWING REVISIONS		
REV. NO.	DATE	DCR NO.

HAMLIN
1993
THIS DESIGN AND PRINT IS COPYRIGHT AND IS THE PROPERTY OF HAMLIN INC. IT MUST NOT BE COPIED OR PERMITTED TO BE COPIED. NOR MUST ITS CONTENTS BE DIVULGED TO ANY THIRD PARTY WITHOUT PRIOR WRITTEN PERMISSION FROM THE COMPANY.

SHEET 1 OF 1 SHEET(S)
DIM.: INCHES (mm)
DWG. NO. 10-5263-1

MDSR-4