
KEMET Part Number: R71VF31004030K

(71VF31004030K)



Capacitor, Film, Metallized Polypropylene, 0.1 uF, +/-10% Tol, -40/+110C, General Purpose, 520 VDC@105C, Lead Spacing=10 mm



General Information	
Supplier:	KEMET
Dielectric:	Metallized Polypropylene
Application:	General Purpose
Sub Application:	Pulse
Style:	Radial Box
Lead Form:	Wire Leads
Features:	Pulse
RoHS:	Yes

Dimensions (mm)		
Symbol	Dimension	Tolerance
L	13	+0.2
Н	11	+0.1
Т	5	+0.2
S	10	+/-0.4
LL	30	+5
F	0.6	+/-0.05

Specifications	
Capacitance:	0.1 uF
Voltage:	520 VDC
Tolerance:	+/-10%
Voltage AC:	250 VAC
Rated Temperature:	105C
Temperature Range:	-40/+110C
Dissipation Factor @ 1 kHz:	0.1%
Dissipation Factor @ 10 kHz:	0.1%
Dissipation Factor @ 100kHz:	0.1%
Insulation Resistance:	100 GOhm
Inductance:	9
Maximum dVdT:	300 v/us
Miscellaneous:	Above 105C DC And AC Voltage Derating Is 4%/C

Packaging Specifications	
Package Kind:	Bulk
Package Quantity:	1500

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

