# BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD





ATS Part#:

#### ATS-50375G-C1-R0

Description:

37.50 x 37.50 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW/maxiGRIP-STD

 Heat Sink Type:
 maxiFLOW

 Heat Sink Attachment:
 maxiGRIP

 Equivalent Part Number:
 ATS-50375G-C2-R0 Discontinued

\*Image above is for illustration purpose only.

### **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock and Unpackaged Drop Testing standards
- Comes preassembled with high performance, phase changing, thermal interface material
- Designed for standard height components from 3 to 4.5mm

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	2.8 °C/W	2.2 °C/W	1.9 °C/W	1.7 °C/W	1.5 °C/W	1.4 °C/W	1.3 °C/W
	Ducted Flow	2.1	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	37.50 mm	37.50 mm	12.50 mm	61.3 mm	T766	BLUE-ANODIZED
<sup>1</sup> /mage above is for illustration purpose only	<ul> <li>Dimensior</li> <li>ATS-5037 (Saint Gol</li> <li>Thermal p application</li> <li>ATS reser performan</li> <li>ATS certifi</li> <li>Optional n</li> </ul>	5G-C2-R0 is the exa bain C1100F). NOTE performance data are n. ves the right to upda nce. ies that this heat sint maxiGRIP™ Installat	mponent size. eight from the botton ict heat sink assembl : Saint Gobain C110 • provided for referen te or change its prod c assembly is RoHS- ion/Removal Tool Se stom options availab	y with an equivalent 0F is discontinued ef ce only. Actual perfo lucts without notice to 6 and REACH compl tt P/N: MGT375	thermal ir ffective 12 rmance m	nterface material 2/31/10. nay vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA