



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE171 Silicon NPN Transistor Audio/Video Amplifier

Description:

The NTE171 is a silicon NPN transistor in a TO202 type case designed for high-voltage TV video and chroma output circuits, high-voltage linear amplifiers, and high-voltage transistor regulators.

Features:

- High Collector-Emitter Breakdown Voltage: $V_{(BR)CER} = 300V$ @ $I_C = 1mA$
- Low Collector-Base Capacitance: $C_{cb} = 3pF$ Max @ $V_{CB} = 20V$

Absolute Maximum Ratings:

Collector-Emitter Voltage ($I_C = 1mA$, $R_{BE} = 10k\Omega$, Note 1), V_{CER}	300V
Collector-Base Voltage, V_{CBO}	300V
Emitter-Base Voltage, V_{EBO}	5V
Collector Current, I_C	
Continuous	100mA
Peak	700mA
Base Current, I_B	250mA
Total Power Dissipation ($T_A = +25^\circ C$), P_D	1.67W
Derate Above $25^\circ C$	13.3mW/ $^\circ C$
Total Power Dissipation ($T_C = +25^\circ C$), P_D	6.25W
Derate Above $25^\circ C$	50mW/ $^\circ C$
Operating Junction Temperature Range, T_J	-55° to $+150^\circ C$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ C$
Thermal Resistance, Junction to Ambient, $R_{\theta JA}$	$75^\circ C/W$
Thermal Resistance, Junction to Case, $R_{\theta JC}$	$20^\circ C/W$
Lead Temperature (During Soldering, 1/16" from case, 10sec), T_L	$+260^\circ C$

Note 1. Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

Electrical Characteristics: ($T_A = +25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF Characteristics						
Collector–Emitter Breakdown Voltage	V _{(BR)CER}	I _C = 1mA, I _B = 0, Note 1	300	–	–	V
Collector Cutoff Current	I _{CBO}	V _{CB} = 300V, I _E = 0	–	–	10	μA
Emitter Cutoff Current	I _{EBO}	V _{BE} = 5V, I _C = 0	–	–	10	μA
ON Characteristics (Note 1)						
DC Current Gain	h _{FE}	I _C = 4mA, V _{CE} = 10V	20	–	–	
		I _C = 20mA, V _{CE} = 10V	30	–	150	
		I _C = 40mA, V _{CE} = 10V	20	–	–	
Dynamic Characteristics						
Current Gain–Bandwidth Product	f _T	I _C = 20mA, V _{CE} = 10V, f = 20MHz	50	–	–	MHz
Collector–Base Capacitance	C _{cb}	V _{CB} = 20V, I _E = 0, f = 1MHz	–	–	3	pF

Note 1. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.

