



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
3. BERYLLIUM COPPER PER QQ-C-530
4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
5. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS				PART NO. SMA7071A2-3GT50G-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED _____ DATE 10-11-01'	
				CHECKED _____ DATE 10-11-01'	
				DRAWN _____ DATE 10-11-01'	
SCALE 8/1 ISSUE A				FILE NO.	

Amphenol	
TITLE SMA FEMALE TO FEMALE ADAPTOR	
DRAWING NO. KJ-SMA7071A2-3GT50G-50	
ITEM NO.	

3	CONTACT PIN	NOTE 3	NOTE 4	1	SMA7071A2-3-A
2	INSULATOR	NOTE 5	NATURAL	2	SMA7071A2-2T-50-B
1	BODY	NOTE 1	NOTE 2	1	SMA7071A2-1-C
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE