LEDDEX

RoHS CE IP 20 4W/M 60LED/M

120° DC 24V

ΡRODUCT DΛΤΛ

Order code LED Type Luminous efficacy Typical luminous flux, lm Wattage Ingress protection Colometric data, CCT Color rendering index LED strip Dimensions , mm

Operating temperature

L80 lifetime

Warranty

LS-L60-4W-XXXXX(24V) 2835 130 lm/W 520 lm/m 4.13 W/m IP 20 3000/4000/6500 K 84 CRI 5000 x 8 x 2 mm -20°C ~ +40°C L80B10 > 36000 hours (@Ta 25 °C) 2 years limited

LS-L60-4V



APPLICATIONS

Signage Accent lighting Furniture



IT IS SPECIFIED

CUT ONLY WHERE

SHIPPING INFORMATION

Single bag quantity Carton box quantity 5m 500m

- This product is only suitable for connection to dedicated Class 1 or Class 2 power supplies rated DC24V (± 5%)
- This product is not to draw a total wattage of greater than the secondary (output) rating of the power supply
- This product is suitable for use in dry locations

VOLTAGE

Specifications of the products might change without further notice. Make sure to use the most recent

Datasheet last updated on 2018-09

LEDDEX, Ltd. Address Elektrines str. 8, Vilnius LT-03150, Lithuania Tel./Fax. +370 5 212 7244 Email info@leddex.eu Website www.leddex.eu