

Technical data sheet

Cable and pipe spacer clip 732 with threaded connection

Art.-Nr. 1360086




St Steel
GTP Electrogalvanised, transparently passivated

Mounting with screw-in spacer clips. Spacer clips and screw-in spacer clips are available in various materials: in V2A stainless steel, in electrogalvanised, hot-dip galvanised steel or in aluminium. Fastening can take place with bolt ties or angler anchors and Sprint screws. Depending on the design, the clips can be "shot" using a bolt-firing tool or nail device.

Master data

Item No.	1360086
Type	732 8 GTP
Description 1	Distance saddle
Description 2	with threaded connection M6
Dimension	7-8mm
Material	Steel
Material symbol	St
Surface finish	Electrogalvanised, transparently passivated
Interface symbol	GTP
Smallest sales unit	100,00 pcs
Weight	1,31 kg/100 pcs.

Technical specifications



Length	34,00 mm
Dimension A	34,00 mm
Dimension B	22,00 mm
Dimension b1	8,00 mm
Dimension t1	1,00 mm
Dimension t2	1,25 mm
Dimension x	1,00 mm
Distance to the wall	☒
Number of cables/pipes	1,00
Version	Closed
Fastening type	Threaded connection
For diameter	7,00 - 8,00 mm
Suitable in fire protection area	☒
Size	-
Halogen-free	☒
Plastic coated	☒
Hole size	M6 mm
Material thickness	1,00 mm
Bolt	M5 x 10
Clamping range D	7,00 - 8,00 mm
UV-resistant	☒